

VERIFICATION OF EMC COMPLIANCE

Verification No.: SZEM2111010030ATV

Applicant: SHENZHEN AKUSENSE TECHNOLOGY CO., LTD

Address of Applicant: 6th Floor, Building A, Xinhui Industrial Park, Tangtou Third Industrial Zone,

Baoan District, Shenzhen, China

Manufacturer: SHENZHEN AKUSENSE TECHNOLOGY CO., LTD

Address of Manufacturer: 6th Floor, Building A, Xinhui Industrial Park, Tangtou Third Industrial Zone,

Baoan District, Shenzhen, China

Factory: SHENZHEN AKUSENSE TECHNOLOGY CO., LTD

Address of Factory: 6th Floor, Building A, Xinhui Industrial Park, Tangtou Third Industrial Zone,

Baoan District, Shenzhen, China

Product Description: Photoelectric Sensors

Model No.: PM18-TM20PO (Please refer to Page 2)

Sufficient samples of the product have been tested and found to be in conformity with

Test Standards: EN IEC 60947-5-2: 2020 Clause 8.2.6 and Clause 9.6

Test Report Number(s): SZEM211101003001

This verification of EMC Compliance has been granted to the applicant based on the results of the tests, performed by laboratory of SGS-CSTC Standards Technical Services Co., Ltd. on the sample of the above-mentioned product in accordance with the provisions of the relevant specific standards under Directive 2014/30/EU.

The CE mark as shown below can be used, under the responsibility of the manufacturer, after completion of an EU Declaration of Conformity and compliance with all relevant EU Directives.



CE

Keny Xu EMC Laboratory Manager

Copyright of this verification is owned by SGS-CSTC Standards Technical Services Co., Ltd. and may not be reproduced other than in full and with the prior approval of the General Manager. This verification is subjected to the governance of the General Conditions of Services which can accessible at https://www.sgs.com/en/terms-and-conditions

Date: 2021-12-10



For Family Model No .:

Code	X1	X2	-	X3	X4	X5	-	X6	X7
Example	PM	18	-	Т	M20	PO			

Code	category	Remark			
X1	Туре	PM/PXM/PSM/:Cylindrical shape			
X2	Thread size	08: M8 12:M12 18: PM18 Vacancy: Non-cylindrical type			
Х3	Types of detection	Vacancy: Diffuse reflection D: Diffuse reflection T: Opposite reflection R: Back light reflection X: Limited reflection			
X4	Sensing distance	Number (detection distance): mm (unit), M + number: M (unit)			
X5	Output type	PO: PNP open-collector, PC: PNP close-collector, NO: NPN open-collector, NC: NPN close-collector, NR: NPN open-collector + NPN close-collector, PR: PNP open-collector + PNP close-collector, N: NPN open-collector + NPN close-collector, P: PNP open-collector + PNP close-collector, AN: indicator light open-collector + NPN, AP: indicator light open-collector + PNP			
X6	Connection	Vacancy: Cable type, W: Cable type, E: Connector			
X7	Agent code	Letters, letters + numbers			